

## Allied Telesis AT-2911SX/SC-901 network card Internal Fiber 1000 Mbit/s

**Brand :** Allied Telesis

**Product code:** AT-2911SX/SC-901

**Product name :** AT-2911SX/SC-901

1000BASE-SX Single-port Fiber NIC for PCIe x1 bus, SC connector, Federal/Government

[Allied Telesis AT-2911SX/SC-901 network card Internal Fiber 1000 Mbit/s:](#)

Allied Telesis AT-2911 Series Network Interface Cards feature a PCI Express (PCIe x1) design, providing the maximum possible bandwidth and bus efficiency while providing the benefits of low power consumption.

### High Reliability

The AT-2911 Series Gigabit interface comes with a comprehensive Microsoft Windows utility which performs detailed tests, diagnostics and analysis.

### Advanced Manageability

The priority queuing offered by the AT-2911 Series can help users set up the network based on their own needs. The comprehensive diagnostics and configuration software suite provides system administrators and engineers with a profound tool to analyze the interface card and check specific data.

Allied Telesis AT-2911SX/SC-901. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Fiber. Maximum data transfer rate: 1000 Mbit/s

| Ports & interfaces                |                                                                                                                                                 | System requirements                 |             |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------|
| Connectivity technology *         | Wired                                                                                                                                           | Windows operating systems supported | ✓           |
| Host interface *                  | PCI Express                                                                                                                                     | Linux operating systems supported   | ✓           |
| Interface *                       | Fiber                                                                                                                                           | <b>Operational conditions</b>       |             |
| Fiber ports quantity              | 1                                                                                                                                               | Operating temperature (T-T)         | 0 - 40 °C   |
| Fiber optic connector             | SC                                                                                                                                              | Storage temperature (T-T)           | -25 - 70 °C |
| <b>Network</b>                    |                                                                                                                                                 | Operating relative humidity (H-H)   | 5 - 90%     |
| Maximum data transfer rate *      | 1000 Mbit/s                                                                                                                                     | <b>Weight &amp; dimensions</b>      |             |
| Networking standards *            | IEEE 802.1p, IEEE 802.1Q, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | Width                               | 87 mm       |
|                                   |                                                                                                                                                 | Height                              | 56 mm       |
| Fiber ethernet cabling technology | 1000BASE-ZX                                                                                                                                     | Weight                              | 700 g       |
| Jumbo frames support              | ✓                                                                                                                                               | <b>Technical details</b>            |             |
| Quality of Service (QoS) support  | ✓                                                                                                                                               | Compliance certificates             | RoHS        |
| <b>Design</b>                     |                                                                                                                                                 | <b>Logistics data</b>               |             |
| Internal *                        | ✓                                                                                                                                               | Harmonized System (HS) code         | 85176990    |
| LED indicators                    | ✓                                                                                                                                               | <b>Other features</b>               |             |
| Certification                     | UL FCC/EN55022 A TUV EN55024 CE C-TICK VCCI                                                                                                     | Flow control support                | ✓           |
| <b>Power</b>                      |                                                                                                                                                 | Management protocols                | SNMP        |
| Output voltage                    | 3.3 V                                                                                                                                           | Link/Act LED                        | ✓           |
| Power consumption (typical)       | 9.2 W                                                                                                                                           |                                     |             |





0767035196619



767035196619

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.