

## Legrand 1LAN-SFP-4305BC-A network transceiver module Fiber optic 1250 Mbit/s

**Brand :** Legrand

**Product code:** 1LAN-SFP-4305BC-A

**Product name :** 1LAN-SFP-4305BC-A

- Up to 1.25Gb/s Data Links
  - Hot-Pluggable
  - Single LC connector
  - Up to 10 km on 9/125µm SMF
  - 1490nm DFB laser transmitter
  - 1310nm PIN photo-detector
  - Single +3.3V Power Supply
  - Monitoring Interface Compliant with SFF8472
  - Maximum Power <1W
  - Industrial operating temperature range: -40°C to 85°C
  - RoHS compliant and Lead Free
- 1000BASE-BX-D BiDi, SFP, 1490nm-TX/1310nm-RX, 10-20km, DOM, LC SMF

Legrand 1LAN-SFP-4305BC-A network transceiver module Fiber optic 1250 Mbit/s:

100% OEM Compatible 1000Base SFP Transceiver (SMF, Tx: 1490 nm Rx: 1310 nm, 20 km, LC, DDM, Industrial Temp.)

Legrand 1LAN-SFP-4305BC-A. SFP transceiver type: Fiber optic, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Metallic, Form factor: SFP. Power consumption (typical): 1 W. Compliance certificates: RoHS. Width: 13.4 mm, Depth: 56.6 mm, Height: 12.8 mm

| Performance                          |                  | Features                          |             |
|--------------------------------------|------------------|-----------------------------------|-------------|
| SFP transceiver type *               | Fiber optic      | Easy to install                   | ✓           |
| Maximum data transfer rate *         | 1250 Mbit/s      | <b>Power</b>                      |             |
| Interface type *                     | SFP              | Power consumption (typical)       | 1 W         |
| Single-mode fiber (SMF) supported    | ✓                | <b>Certificates</b>               |             |
| Fiber optic connector                | LC               | Compliance certificates           | RoHS        |
| SFP transceiver standard             | BX-D             | <b>Operational conditions</b>     |             |
| Maximum transfer distance            | 20000 m          | Minimum operating temperature     | -40 °C      |
| Tx wavelength (max)                  | 1310 nm          | Maximum operating temperature     | 85 °C       |
| Rx wavelength (max)                  | 1490 nm          | Operating temperature (T-T)       | -40 - 85 °C |
| Ethernet interface type              | Gigabit Ethernet | Storage temperature (T-T)         | -40 - 85 °C |
| Fiber ethernet cabling technology    | 1000BASE         | Operating relative humidity (H-H) | 0 - 85%     |
| Digital Diagnostics Monitoring (DDM) | ✓                | <b>Weight &amp; dimensions</b>    |             |
| <b>Features</b>                      |                  | Width                             | 13.4 mm     |
| Product colour                       | Metallic         | Depth                             | 56.6 mm     |
| Form factor                          | SFP              | Height                            | 12.8 mm     |
| Plug and Play                        | ✓                | <b>Packaging content</b>          |             |
| Hot-Plug support                     | ✓                | Quantity per pack                 | 1 pc(s)     |



## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.