



Canon EOS R10 Content Creator Kit MILC 24.2 MP CMOS 6000 x 4000 pixels Black

Brand : Canon

Product family: EOS

Product code: 5331C079

Product name : EOS R10
Content Creator Kit

- Capture sharp photos and video
- Full features, sleek design
- Capture fast-moving subjects in brilliant detail
- Smart, speedy autofocus

EOS R10 Content Creator Kit

Canon EOS R10 Content Creator Kit. Camera type: MILC, Megapixel (approx.): 24.2 MP, Sensor type: CMOS, Maximum image resolution: 6000 x 4000 pixels. ISO sensitivity (max): 32000. Optical zoom: 2.5x, Focal length range: 18 - 45 mm. Wi-Fi. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels. Display diagonal: 7.49 cm (2.95"), Touchscreen. PictBridge. Weight: 382 g. Product colour: Black

Picture quality		Display	
Image sensor aspect ratio	3:2	Viewing angle, horizontal	150°
Camera type *	MILC	Viewing angle, vertical	150°
Megapixel (approx.) *	24.2 MP	Anti-smudge coating	✓
Sensor type *	CMOS	Display brightness adjustment	✓
Maximum image resolution *	6000 x 4000 pixels	Number of manual brightness adjustment levels	7
Sensor cleaning system name	EOS Integrated Cleaning System	Number of colour tone adjustment settings	4
Still image resolution(s) *	6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600 6000 x 3368, 3984 x 2240, 2976 x 1680, 2400 x 1344 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600	Viewfinder	
		Viewfinder type	Electronic
		Magnification	0.95x
		Viewfinder screen size	0.39"
Image stabilizer *	✓	Viewfinder information AE lock, AEB, AF method, AF operation, AF point information, Anti-flicker shooting, Aperture, Aspect ratio, Battery level, Bluetooth function, Digital Lens Optimizer, Electronic level, Exposure compensation, Exposure level indicator, Exposure simulation, FE lock, FEB, Flash off, Flash-ready, Focus distance scale, Grid, HDR shooting, High-speed sync, Highlight tone priority, Histogram, ISO speed, Image Quality, Lens information, Maximum burst, Metering mode, Multi Shot Noise Reduction, Multi-function lock warning, Multiple-exposure shooting, Number of remaining multiple exposures, Number of self-timer shooting, Picture Style, Vertical exposure scale, White balance correction, Wi-Fi function	
Image stabilizer location	Lens		
Supported aspect ratios	1:1, 3:2, 4:3, 16:9		
Total megapixels	25.5 MP		
Image sensor size (W x H)	22.3 x 14.9 mm		
Sensor format	Advanced Photo System type-C (APS-C)		
Built-in low-pass filter	✓		
Colour filter type	Primary colour filter		
Number of compressed options (JPEG)	2		
Number of compressed options (HEIF)	2		
Simultaneous recording modes	RAW + JPEG RAW + HEIF		
Image formats supported *	C-Raw, EXIF, HEIF, JPEG, Raw		
Lens system		Ports & interfaces	
Optical zoom *	2.5x	PictBridge *	✓
Focal length range	18 - 45 mm	USB version *	2.0
Minimum focal length (35mm film equiv)	29 mm	USB connector	USB Type-C
Maximum focal length (35mm film equiv)	72 mm	HDMI *	✓
Lens structure (elements/groups)	7/7	HDMI connector type	Micro
Lens type	Wide-angle zoom	Microphone in	✓
Filter size	49 mm		
Number of diaphragm blades	7		
Lens 2 minimum aperture number	4.5		
Lens 2 maximum aperture number	6.3		
Lens 2 structure (elements/groups)	7/7		

Lens system		Network	
Lens mount interface	Canon RF	Bluetooth *	✓
Focusing		Bluetooth version	4.2
Focus *	TTL	Wi-Fi *	✓
Focus adjustment *	Auto/Manual	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Focusing system	Dual Pixel CMOS AF II	Camera	
Auto focusing (AF) modes *	One Shot Focus, Spot Auto Focus, Servo Auto Focus	White balance *	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Shade, Tungsten
Auto Focus (AF) object detection	Animal, Eye, People, Bird, Face	White balance compensation (Blue/Amber)	±9
Face tracking	✓	White balance compensation (Magenta/Green)	±9
Auto Focus (AF) points	651	Custom white balance	✓
Auto Focus (AF) points selection	Auto, Manual	Number of custom white balance settings	5
Auto Focus (AF) area (auto selection) (horizontal/vertical)	100/100%	Scene modes *	Fine detail, Landscape, Monochrome, Panorama, Portrait, Standard
Auto Focus (AF) area (manual selection) (horizontal/vertical)	90/100%	Shooting modes *	Aperture priority, Auto, Manual, Program, Scene, Shutter priority
Auto Focus (AF) points manual selection	AF point expansion 4 points, AF point expansion surrounding, Flexible zone AF 1-3	Self-timer delay *	2,10 s
Auto Focus (AF) lock	✓	Brightness adjustment	✓
Auto Focus (AF) assist beam	✓	Camera playback	Movie, Single image, Slide show, Thumbnails
Exposure		Languages support	Multi
ISO sensitivity (min) *	100	Histogram	✓
ISO sensitivity (max) *	32000	Image editing	Crop, Resizing
Light exposure modes *	Auto	Orientation sensor	✓
Light exposure value	EV -4 - 20 (23 °C, ISO 100)	Camera file system	DCF 2.0, DPOF 1.1, Exif 2.31, Raw
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)	High Dynamic Range (HDR) supported	✓
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot	Colour space supported	RGB
Auto Exposure (AE) lock	✓	Image crop aspect ratios	1:1, 3:2, 4:3, 16:9
Auto Exposure (AE) locking (auto)	Focus achievement	Multiple exposure	✓
Auto Exposure (AE) locking (manual)	AE lock button (P, Av, Fv, Tv, M modes)	RAW image processing	✓
Number of measurement zones	384	High Dynamic Range (HDR) video processing	✓
Exposure bracketing (AEB)	± 3EV (1/2EV; 1/3EV stop)	HEIF to JPEG conversion	✓
Anti-flicker shooting	✓	Camera drive modes	Continuous high, Continuous high+, Continuous low, Self-timer, Single
Flicker detection frequency	100 - 120 Hz	Built-in interval timer	✓
Shutter		File numbering options	Auto-reset, Consecutive numbering, Manual reset
Fastest camera shutter speed *	1/16000 s	Metadata supported	✓
Slowest camera shutter speed *	30 s	Histogram options	Brightness, RGB
Camera shutter type	Electronic, Mechanical	Erase options	Folder, Memory card, Select range, Selected images, Single image
Camera shutter speed (bulb electronic)	1/16000 s	Erase protection options	Folder, Memory card, Single image
Shutter release type	Electromagnetic	Menu categories	AF Menu, Custom functions menu, My Menu, Network, Playback menu, Setup menu, Shooting menu
Flash		Firmware upgradeable	✓
Flash modes *	Second curtain synchro	Tripod mounting supported *	✓
Flash exposure lock	✓	Slideshow	✓
Flash guide number	6 m	Slideshow setting	All, Date, Folder, Images, Protected images, Rating, Videos
Flash recharging time	5 s	Slideshow playback time	1, 2, 3, 5, 10, 20 s
Flash exposure compensation	✓	Built-in processor	✓
Flash exposure correction	±3EV (1/2; 1/3 EV step)	Image processor	DIGIC X
Shoe mounting point	✓		
Shoe mounting point type	Hot shoe		
Flash exposure bracketing	✓		
Brand specific flash systems	E-TTL II (Canon)		
Wireless multi-flash support	✓		
Video			
Video recording *	✓		
Maximum video resolution *	3840 x 2160 pixels		

Video		Camera			
HD type *	4K Ultra HD	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64		
Video resolutions	3840 x 2160,1920 x 1080 pixels				
Video formats supported	H.264, H.265, MPEG4, HEVC				
Dual card video recording	✗				
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit				
Audio		Mac operating systems supported	Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 11.0 Big Sur		
Built-in microphone *	✓				
Audio formats supported	AAC, PCM				
Memory					
Compatible memory cards *	SDXC, SD, SDHC				
Memory slots	1	Design	Black		
Memory card read mechanism	UHS-II				
Display					
Display *	TFT				
Touchscreen *	✓				
Display diagonal *	7.49 cm (2.95")	Battery	Lithium-Ion (Li-Ion)		
Display diagonal (metric)	7.5 cm				
Display resolution (numeric)	1040000 pixels				
Flip-out screen	✓				
Field of view	100%				
		Power	430 shots		
		Operational conditions	0 - 40 °C		
		Weight & dimensions	0 - 85%		
		Packaging content	122.5 mm		
		Technical details	83.4 mm		
			87.8 mm		
			382 g		
			429 g		
			4.43 cm		
			130 g		
			24.2 MP		
			2 h		



0660685245150



660685245150

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.